



www.ipc-markt.de

# NOAH - MMC

## Designer-PC mit Pentium M oder CoreDuo CPU (Lüfterlos mit Heatpne)



### Mechanisch

Laufwerke : 1 x 3.5" / Slim LW Schacht

- LED Anzeigen  
Power und HDD Activity
- Switches: Power und Reset
- Front connections : USB2.0 x 2, Audio
- FireWire (IEEE1394)
- Material: beschichtetes Stahlblech mit  
Formschöner Aluminum Front Blende
- Ext. Netzteil 110-230 VAC auf 19VDC
- Abmessungen :  
202 x 97 x 273mm (B x H x T)

### Variante 2 (Pentium M CPU) i915 GMt

#### Specification

**CPU Socket** Socket 478  
Supports Intel® Pentium M Processor up to 1.6 GHz

**Chipset** Intel® 915GM ICH6-M

**CPU Front Side Bus (FSB)** : 533 MHz

**BIOS** Award BIOS, ACPI supported

**System Memory**  
2 x DDR2 400/533 bis 2 GB

**Integrated VGA**  
Intel® 915 GM VGA for CRT/TV out  
Supports DVM T 3.0 for memory allocation

Graphik  
**One D-SUB VGA Output, SVIDEO Connector**

**LAN**  
Intel 10/100 /1000 BaseT Ethernet

**Audio**  
ICH7M integrated audio with AC97 codec, SP-DIF Connector

**Multi I/O**  
ICH6M, Winbond W83627EHF chipset  
Supports 1x IDE, 2x SATA, 2x RS-232, 1x FDD, 1x KB, 1x Mouse

**IDE Interface**  
Built in ICH6M; One enhanced IDE channel supports  
2 IDE devices; supports UDMA33/66/100  
**Serial ATA** Supports 2 ports

**FDD Interface** Onboard slim FDD connector  
**Serial Ports** Two RS-232 ports  
**1394** Supports 2 ports (TI TSB43LV22)

**USB (2.0)**  
Supports 6 USB ports (4 ports + 2 ports via pin header)

### Variante 1 (CoreDuo /Solo CPU ) i945 GTt

#### Specification

**CPU Socket** Socket 478  
Supports Intel® Core™ Duo (Yonah) / Solo processor up to 2.33GHz

**Chipset** Intel® 945GM chipset ICH7M

**CPU Front Side Bus (FSB)** 533MHz / 667MHz

**BIOS** Award BIOS, ACPI supported

**System Memory**  
2 x So-DIMM 400/533/667 DDR2 bis 2 GB

**Integrated VGA**  
Intel® 945GM integrated VGA for CRT/TV out  
Supports DVM T 3.0 for memory allocation

**LVDS**  
Intel® 945GM integrated for 18-bit dual channel LVDS  
Optional ID390 with Chronitel 7308 for 24-bit LVDS

**VGA Options**  
Optional single/dual DVI cards with connectors on card or via cable

**LAN**  
Intel 10/100 /1000 BaseT Ethernet

**Audio**  
ICH7M integrated audio with AC97 codec  
Onboard NS LM4950 amplifier

**Multi I/O**  
ICH7M, Winbond W83627EHF chipset  
Supports 1x IDE, 2x SATA, 2x RS-232, 1x FDD, 1x KB, 1x Mouse

**IDE Interface**  
Built in ICH7M; One enhanced IDE channel supports  
2 IDE devices; supports UDMA33/66/100

**Serial ATA** Supports 2 ports , support Raid 0,1

**FDD Interface** Onboard slim FDD connector

**Expansion**  
Mini PCI, PCI-E(1),

**Serial Ports** Two RS-232 ports  
**1394** Supports 2 ports (TI TSB43LV22)

**USB (2.0)**  
Supports 6 USB ports (4 ports + 2 ports via pin header)  
**IrDA** by Pin header



i945 GTt



i915 GMt