

HI-19MT-PCAP

19" LED-Backlight LCD Monitor with Projected Capacitive Multi-Touch



Features


- Coated, antiglare Security Glas Panel
- **19" Multi-Touch Screen**
- VGA, DVI
- **Scratch – Resistance**
- **IP54 - Dust and Water Resistant.**
- Excellent Brightness & Contrast
- Perfect Picture Performance
- Adjustable Picture Proportions
- Pivot Function
- VESA- Holder
- Panel Mounting
- Full Metall Sheet Chassis for optimal electrical and thermal protection

Model NO.	HI-19MT- PCAP
Viewing Area	19"
Touchscreen	Projected Capacitive, Multitouch
Resolution	1280 x 1024 (1.3 megapixel)
Display Area	301.1 x 376.5 mm
Contrast	1 000 : 1 with touch panel
Colors	16,7 Mio
Response Time	5 ms
Brightness	225 cd/qm
Viewing Angle	H 170 x V160
Input Signal	DVI/ D, VGA (D-Sub)
Input Connector	DVI/ D, VGA (D-Sub), USB
Scan Frequency	H:31,4-80 KHz V: 56-75Hz
VESA Mounting	100 x 100 mm Standard
Consumption	25 W typical; max. 2 W in Power management mode
Dimensions (mm)	See Drawing
Op. Temperature	0 - 45 Degr. C
Weight	5,8KG
Standard	IP-54 (Front) CE, TÜV, CB,

Optional Accessories



**Holder for Mini-IPC
Back-Site Mounting**



Swingarm

**Additional : Wallmount Kits
(fix or turnable)**

19" Panel-Mounting

