

## Industrial Monitor HI-22W-T

The Versatile 22" Widescreen TFT Touch Monitor



### Features


- Excellent Brightness & Contrast
- 4 Industrial Inputs :  
VGA, DVI, S-Video ,Video Composite
- **16:10 Presentation**
- 5 Wire resistive Touchscreen (RS/232 or USB )
- Capacitive Touchscreen (optional)
- 24/7 Operation (Dauerbetrieb)
- VESA- Holder
- Panel Mounting
- Full Metall Sheet Chassis for optimal electrical and thermal protection

Model NO.	HI-22W-T	
Viewing Area	22" Widescreen	
Touchscreen	E-Turbo	5 Wire resistive
Resolution	1680 x 1050	WSXGA
Eff. Display Area	475 x 297	mm
Colors	16,7 Mio	
Response Time	3/3 ms	
Contrast Ratio	1000 : 1	
Brightness	300 cd/qm	
Viewing Angle	H 170 x V160	
Input Signal	Analog VGA /	DVI / S-Video Comp. Video
Input Connector	D-sub 15pin /	DVI /Cinch
Scan Frequency	H:30- 94 KHz	V: 50-80Hz
Power Mgmt	VESA DPMS	Standard
Consumption	50W @12VDC	Opt. Extern. 12 V Adapt.
Dimensions (mm)	See Drawing	
Op. Temperature	0-50 Degr. C	
Weight	6,9KG	
Standard	IP-65 (Front)	(Optional)

### Optional Accessories



**Holder for Mini-IPC  
Back-Site Mounting**



**Swingarm**

**Additional : Wallmount Kit**

### 22" Panel-Mounting

