




www.ipc-markt.de

# Industrial Monitor HI-32

## Multimedia Widescreen TFT (16 : 10)

### with horizontal and Portrait-Presentation



## Features

- Coated, antiglare Security Glas Panel
- Excellent Brightness & Contrast
- 6 Inputs :  
HDMI, VGA, DVI, S-Video, Video Composite, Component Video
- **16:10 Presentation**
- VESA- Holder
- Horizontal/vertical Mounting
- Full Metall Sheet Chassis

Model NO.	HI-32	
Viewing Area	32"	Widescreen
Touchscreen		Option Infrared
Resolution	1366 x 768 /	1900 x 1200 (interl.)
Eff. Display Area	698 x 392	mm
Colors	16,7 Mio	
Response Time	8/8 ms	
Contrast Ratio	4000 : 1	
Brightness	450 cd/qm	
Viewing Angle	H 178 x V178	
Input Signal	Analog VGA / S-Video	DVI / HDMI / Comp. Video
Input Connector	D-sub 15pin /	DVI /Cinch
Scan Frequency	H: 49 KHz	V: 60 Hz
Power Mgmt	VESA DPMS	Standard
Consumption	130W	
Dimensions (mm)	768x458x113	WxHxD mm
Op. Temperature	0-50 Degr. C	
Weight	19 KG	
Standard	IP-65 (Front)	(Optional)

## Optional Accessories



**Holder for Mini-IPC  
Back-Site Mounting**

## 32" Mounting Options



**Optional : Wallmount Kit**

**Table Stand Type A –  
Landscape (Option)**



**Table Stand Type B – Portrait/  
Landscape (Option)**

