




www.ipc-markt.de

# Industrial Monitor HI-42ML



## Features

- Coated Protective Security Glas
- Excellent Brightness & Contrast
- 6 Inputs :  
HDMI, VGA, DVI, S-Video, Video Composite, Component Video
- **Portrait & Landscape (16: 9) Presentation**
- VESA- Holder
- Full Metall Sheet Outdoor Chassis

Model NO.	HI-42ML	
Viewing Area	42"	Widescreen
Touchscreen		Option : Infrared
Resolution	1366 x 768	1900 x 1200 (interl.)
Eff. Display Area	930 x 523	mm
Colors	16,7 Mio	
Response Time	8/8 ms	
Contrast Ratio	800 : 1	
Brightness	500 cd/qm	
Viewing Angle	H 178 x V178	
Input Signal	Analog VGA / SVideo	DVI / HDMI / Comp. Video
Input Connector	D-sub 15pin /	DVI /Cinch
Scan Frequency	H: 49 KHz	V: 60 Hz
Power Mgmt	VESA DPMS	Standard
Consumption	220W	
Dimensions (mm)	987x580x120	WxHxD mm
Op. Temperature	0-50 Degr. C	
Weight	32 KG	
Standard	IP-65 (Front)	(Optional)

## Optional Accessories



**Holder for Mini-IPC  
Back-Side Mounting**

## 42" Mounting Options



**Table Stand Type A – landscape (Option)**

**Table Stand Type B – portrait/ landscape**

**Optional : Wallmount Kit**