

HI-42MT

Industrial Multitouchscreen Monitor

Features



- Excellent Brightness & Contrast
- Optical Touchscreen Technology
- NeoV™ Touch Glas-Surface
- 5 Inputs :
VGA, DVI, S-Video,
Video Composite, Component Video
- PIP-, PBP- and VOV-Funktion
- Integrated Speakers
- Remote Control
- VESA- Holder
- Horizontal/vertical Mounting (Pivot)
- Full Metall Sheet Chassis

Model NO.	HI - 42MT	
Viewing Area	42"	Full HD
Touchscreen		Optical via USB
Resolution	1920x1080	
Eff. Display Area	930 x 523	mm
Colors	16,7 Mio	
Response Time	6/6 ms	
Contrast Ratio	4000 : 1	
Brightness	450 cd/qm	
Viewing Angle	H 178 x V178	
Input Signal	Analog VGA / SVideo	DVI Comp. Video
Input Connector	D-sub 15pin /	DVI /Cinch
Scan Frequency	H: 49 KHz	V: 60 Hz
Power Mgmt	VESA DPMS	Standard
Consumption	220W	
Dimensions (mm)	987x580x120	WxHxD mm
Op. Temperature	0-50 Degr. C	
Weight	27 KG	
Standard	IP-65 (Front)	(Optional)

Optional Accessories



**Holder for Mini-IPC
Back-Site Mounting**

42" Mounting Options



Table Stand Type A – landscape (Option)

Table Stand Type B – portrait/ landscape

Optional : Wallmount Kit