

Public Display PD-42

Outdoor Display w/ 42" TFT

with horizontal and Portrait-Presentation

Features



- Coated, antiglare Security Glas Panel
- Excellent Brightness & Contrast
- 6 Inputs : HDMI, VGA, DVI, S-Video, Video Composite, Component Video
- **16:10 Presentation**
- VESA- Holder , horizontal/vertical Mounting
- Full Metall sheet Chassis



Model NO.	PD-42ML	
Viewing Area	42"	Widescreen
Touchscreen		Option : Infrared
Resolution	1366 x 768	1900 x 1200 (interl)
Eff. Display Area	930 x 523	mm
Colors	16,7 Mio	
Response Time	8/8 ms	
Contrast Ratio	800 : 1	
Brightness	500 cd/qm	
Viewing Angle	H 178 x V178	
Input Signal	Analog VGA / SVideo	DVI / HDMI / Comp. Video
Input Connector	D-sub 15pin /	DVI /Cinch
Scan Frequency	H: 49 KHz	V: 60 Hz
Power Mgmt	VESA DPMS	Standard
Consumption	220W	
Dimensions (mm)	987x580x120	WxHxD mm
Op. Temperature	0-50 Degr. C	
Weight	32 KG	
Standard	IP-65 (Front)	(Optional)

Optional Accessories



Holder for Mini-IPC
Back-Side Mounting

42" Mounting Options



Table Stand Type A – landscape (Option)

Table Stand Type B – portrait/ landscape

Optional : Wallmount Kit