

IEC-740

Full-size, 6-slot Wallmount Chassis

- ISA, PISA or PCI/ISA Backplane
- 250 W Power Supply"



General Specifications

Construction

heavy-duty steel

Disk Drive Capacity

two 3½" drives

LEDs

power On/Off, HDD on front

Controls

reset on front panel

Cooling Fan

one 49 CFM cooling fan on front panel with air filter

Dimensions

169.2 (W) x 240 (H) x 400.2 (D) mm

Weight

8 Kgs

Environmental

Operating Temperature

0 to 50°C

Relative Humidity

10 to 95%

Vibration (operating)

5 to 17 Hz, 0.1" double-amplitude displacement; 17 to 500 Hz, 1.5 G acceleration peak to peak

Shock (operating)

10 G acceleration peak (11 ms duration)

EMI

meets FCC/DE
Class A



Passive Backplane Options

PBI-6SA

6-slot ISA-bus Passive Backplane

PBPI-6SA

6-slot PICMG Passive Backplane

1 x ISA, 4 x PCI and 2 x PICMG

PBP-5S

5-slot PISA Passive Backplane

3 x PCI and 3 x PISA

Power Supply Options

IPS-ZKS-250A

250 W Power Supply (PS/2 size)

V_{INPUT} : 95~130 V_{AC} or 180~260 V_{AC}
@ 47~63 Hz, switchable

V_{OUTPUT} (max. load) : +5 V @ 25 A,
+12 V @ 10 A, -5 V @ 0.5 A, -12V @ 0.5 A

V_{OUTPUT} (min. load) : +5V @ 1 A, +12 V @ 0.4 A

Ordering

IEC-740-S6A-AT250 Full-size Wallmount Chassis with 6-slot ISA Passive Backplane and 250 W Standard Power Supply

IEC-740-C6A-AT250 Full-size Wallmount Chassis with 6-slot PCI/ISA Backplane and 250 W Standard Power Supply

IEC-740-P5-AT250 Full-size Wallmount Chassis with 5-slot PISA Passive Backplane and 250 W Standard Power Supply

