



www.ipc-markt.de

Modular Panel - IPC with fanless Mini - IPC



Features

- 19" (Rack) - or Panel-Mounting
- Fully Modular Concept :
Two Units : TFT and Mini-IPC
- 12"-, 15"-, 17" – 19" or 20" TFT's
- Steel Metalhousing for optimum thermal and electrical protection
- Fanless Operation with Heatpipe
- Fanless Pentium M, Intel Core Duo or VIA CPU's
- AC97 Audio Codec
- Single or Dual Ethernet
- 6 x USB-Ports / 2 x Com-Ports / LPT
- 1 or 2 PCI Slots
- Watch Dog Timer & Hardware Monitoring (Pentium M)
- Depth only 135 mm
- Hard Disk and CD-ROM protected against shock & vibration through patented shockabsorbers
- Mounting Kits for 12", 15"-, 17"-, 19" and 20" – TFT Displays
- Touch Screen Option

Specification

Low Power fanless Intel Pentium M Processor (Centrino)

- Socket 478 for Intel Pentium M Processor up to 1.8 GHz
- Hyper Threading Technology
- 400 MHz FSB (533 MHz at 1.8 GHz CPU)
- Fanless Operation with Heatpipe
- Intel 855 GM/E Chipset
- Chipset Integrated LVDS/VGA Function
- AC97 Audio Codec
- Gigabit LAN -10/100/1000 Base TX Ethernet
- 6 x USB-Ports/ 2 Com-Ports (RS-232/422)
- 1 or 2 PCI Slots, PC-Card Slot, Compact Flash Socket
- Watch Dog Timer & Hardware Monitoring

Fanless Intel CoreDuo (& CoreSolo) CPU

- Socket 478 for Intel CoreDuo CPU T2300...T2600
- Mobile Intel®; 945GM Chipset
- Supports CRT, LVDS, optional TV out or DVI
- Dual LAN - 10/100 BaseT & PCI Express Gigabit LAN
- SATA x 2, 6 x USB, IDE, RS-232
- One or two PCI-Slots (with Riser Card)
MiniPCI, PCI-E(1), Mini PCIe

Low Power Fanless on Board VIA Eden Processor

up to 1GHz

- 2 x RS/232, LPT1, 2 x USB, IDE-, Floppy Controller
- LAN (100 Mbit/s)
- Chipset Integrated LVDS/VGA Function

TFT Family

15" Display

Resolution XGA 1024 x 768, 0,297 mm
500cd/m², Contrast : 400:1
11,5 / 5 ms Resp.Time

17" Display

Resolution SXGA 1280x1024, 0,264 mm
250cd/m², Contrast : 500:1
15 / 10 ms Resp.Time

19" Display

Resolution SXGA 1280x1024, 0,294 mm
300cd/m², Contrast : 700:1
15 / 10 ms Resp.Time

20" Display

Resolution UXGA 1600x1200, 0,255 mm
250cd/m², Contrast : 600:1
15 / 10 ms Resp.Time

Option : resistive Touch Screen for all TFT

Power Supply :

110-240 VAC, or 12/24 VDC for mobile applications

Environmental

Operating Temperature : 0 ... 60 ° C

Storage : -20 ... 80 ° C

Rel. Humidity : 10% .. 90 % (non-condensing)

Weight : 9 KG

Dimensions : Depending of TFT Size
Depth = 135 mm

Approval : CE