

Compact Touchscreen Panel-PC Family

**CPC-800T CPC-1000T CPC-1200T
CPC-1500T**



Features

- **Industrial Panel PC with 8", 10", 12" or 15" TFT**
- **Panel- or 19"- (Rack-) Mounting (opt.)**
- **Low Power Intel Atom N270 CPU**
- **1 GB RAM**
- **2 ½" Disk**
- **onboard SSD with 6 GB max**
- **GB LAN**
- **7 x USB-Ports , PCIe**
- **5 x RS/232/422**
- **2x SATA , PCIe**
- **1 x Mini PCI Card Socket**
- **CF-Card Slot**
- **Resistive 5 Wire Touch Screen**
- **VESA Mounting**

Specification

Ultra Low Power Fanless on Board Intel Atom CPU N270 (1.8 GHz)

- Intel® 945GSE Chipset & Intel ICH7M (82801GBM)
- FSB 533 MHz
- 1 GB RAM
- onboard SSD with 2/4/6GB
- 2 x SATA
- 1 x GB LAN
- VGA DVM T 3., Resolution up to SXGA+
- Chipset Integrated LVDS/VGA Function
- 7 x USB
- 5 x RS232 /422
- 1 PCIe
- Mini-PCI Card Socket
- CF-Card Slot

Resolution

CPC-800	8" TFT	800 x 600
CPC-1000	10" TFT	800 x 600
CPC-1200	12" TFT	1024 x 768
CPC-1500	15" TFT	1024 x 768

Resistive Touchscreen

External Power Supply 12 V DC (opt. 24 VDC)

Environmental :

Operating Temp : 0 ... 45 Degree C


Weight : 1.6 KG

Dimensions :


CPC-1200 : 356x326 mm (BxH) Panel

Approval : CE

Mounting Options



Swing Arm Mounting



Panel Mounting (Dimensions)
CPC-1200: 356 x 328 mm (BxH)



19" Mounting with Mounting Kit