



www.ipc-markt.de

WS-1500

19"- Industrial Workstation , 6HU
with fanless Mini-IPC



Front Stainless Steel

Display 15" High Resolution TFT

Resolution XGA 1024 x 768, 0,297 mm Pitch
400cd/m² , Contrast : 400:1
11,5 / 5 ms Response Time

Keyboard Waterproof Full Function Membrane Keyboard

Mousepad Waterproof Membrane Touchpad

CPU 's

Low Power fanless Intel Pentium M Processor (Centrino)

- Socket 478 for Intel Pentium M Processor up to 1.8 GHz
- Hyper Threading Technology
- 533 MHz FSB
- Intel 855 GM/E Chipset
- Chipset Integrated LVDS/VGA Function
- GB LAN
- 6 x USB-Ports/ 2 Com-Ports (RS232/422)
- PC-Card Slot, Compact Flash Socket
- Watch Dog Timer & Hardware Monitoring

Fanless Intel CoreDuo (& CoreSolo) CPU

- Socket 478 for Intel CoreDuo CPU T2300...T2600
- Mobile Intel[®] 945GM Chipset
- Supports CRT, LVDS, optional TV out or DVI
- 2 x GB LAN
- SATA x 2, 6 x USB, IDE, RS-232 (442 opt..)
PCI-Slot , MiniPCI, Mini PCIe

Fanless Low Power onBoard Intel ATOM CPU

- Intel ATOM N270 CPU @ 1,6 GHz
- Intel -945 Chipset + ICH7 , Integrated Intel GMA950
- FSB 400/533 MHz , 1 GB L2 Cache
- 5 x RS232/422/485 , LPT1, 6 x USB, SATA x 2 , IDE
- 2 x GB LAN

Features

- Most Compact Workstation for Pentium M and CoreDuo fanless CPU's
- 19" Mounting , only 6 HU (266 mm)
- 15" High Resolution TFT
- Steel Metalhousing for optimum thermal and electrical protection
- Fanless Operation with Heatpipe
- AC97 Audio Codec
- 1 or 2 x GB LAN
- 6 x USB-Ports / 4/5 x Com-Ports / LPT
- 1 or 2 PCI Slots with RiserCard
- Depth only 135 mm
- Hard Disk and CD-ROM protected against shock & vibration through patented shockabsorbers
- Touch Screen Option



Workstation in Rittal Enclosure



Workstation with 4 Front USB--Connectors

Power supply : 110-240 VAC
or 12/24 VDC

Weight : 8 KG

Operating Temperature : 0 .. .55 ° C

Dimensions

482 mm (W) x 135 mm (D) x 266 (H)

Option : **resistive Touch Screen**

Approval : CE, FCC