



# Em104P-SCSI-U2

## Ultra2 LVD SCSI Module

**Protocols Supported**  
Ultra2 LVD, Ultra-Wide SCSI

**SCSI Processor**  
LSI Symbios 895

**Max Transfer Rate**  
80 MB/s (Ultra2)

**Max. Devices Supported**  
15

**Connector**  
external 68-Pin LVD

**Cable length**  
LVD SCSI Cable length up to 12 meters

**PCI standards**  
PCI 2.1 compliant with full Plug & Play support

Level triggering allows interrupt sharing between multiple adapters  
High speed 32-bit PCI bus master DMA transfers up to 133 MB/s in burst mode

**OS Support**  
DOS, Windows, Windows NT, OS/2, NetWare, Linux(Red Hat, Caldera, SlackWare, Turbo-Linux, S.U.S.E. and Debian), FreeBSD, Solaris, SCO Unix and Unixware

**Pressfit PC/104 Connectors**  
High quality pressfit connectors for ISA and PCI bus to guarantee optimal connection and fit

### Ordering

Em104P-SCSI-U2D : *PC/104-Plus*  
Ultra2 LVD SCSI Module  
with LSI Symbios 896



# Em104P-SCSI-U2D

## Dual Ultra2 LVD SCSI

**Protocols Supported**  
Ultra2 LVD, Ultra-Wide SCSI

**SCSI Processor**  
LSI Symbios 896

**Max Transfer Rate**  
80 MB/s (Ultra2)

**Max. Devices Supported**  
30 (2x 15)

**Connector**  
dual external 68-Pin LVD

**Cable length**  
LVD SCSI Cable length up to 12 meters

**PCI standards**  
PCI 2.1 compliant with full Plug & Play support

Level triggering allows interrupt sharing between multiple adapters.  
High speed 32-bit PCI bus master DMA transfers up to 133 MB/s in burst mode

**OS Support**  
DOS, Windows, Windows NT, OS/2, NetWare, Linux(Red Hat, Caldera, SlackWare, Turbo-Linux, S.U.S.E. and Debian), FreeBSD, Solaris, SCO Unix and Unixware

**Pressfit PC/104 Connectors**  
High quality pressfit connectors for ISA and PCI bus to guarantee optimal connection and fit

### Ordering

Em104P-SCSI-U3D : *PC/104-Plus*  
Dual Channel Ultra2 LVD SCSI Module  
with LSI Symbios 896



# Em104P-SCSI-U3D

## Dual Ultra3 LVD SCSI

**Protocols Supported**  
Ultra3 LVD, Ultra2 LVD, Ultra-Wide SCSI

**SCSI Processor**  
LSI Symbios 1010-33

**Max Transfer Rate**  
160 MB/s (Ultra3)

**Max. Devices Supported**  
30 (2x 15)

**Connector**  
dual external 68-Pin LVD

**Cable length**  
LVD SCSI Cable length up to 12 meters

**PCI standards**  
PCI 2.1 compliant with full Plug & Play support

Level triggering allows interrupt sharing between multiple adapters  
High speed 32-bit PCI bus master DMA transfers up to 133 MB/s in burst mode

**OS Support**  
DOS, Windows, Windows NT, OS/2, NetWare, Linux(Red Hat, Caldera, SlackWare, Turbo-Linux, S.U.S.E. and Debian), FreeBSD, Solaris, SCO Unix and Unixware

**Pressfit PC/104 Connectors**  
High quality pressfit connectors for ISA and PCI bus to guarantee optimal connection and fit

### Ordering

Em104P-SCSI- U3D : *PC/104-Plus*  
Dual channel Ultra2 LVD SCSI Module  
with LSI Symbios 1010-33