



www.ipc-markt.de

# HDTV Media Terminal

The optimum Viewing Point on Exhibitions & Showrooms



Superslim Media Terminal in Stainless Steel or Aluminum Housing System

- 42" - High Brightness TFT (Option 55") with **HDTV** Resolution
- Brightness up to 600 cd/qm
- Touchscreen Option

**including fanless Industrial - PC**

- **Intel ATOM / PentiumM or Core2Duo CPU**
- Wireless LAN Module

## Specification

### 1. Ultra Low Power fanless on Board Intel Single or Dual Core Atom Processor

- Intel<sup>®</sup>: 945GM Chipset
- 2 x RS/232, LPT1, 4 x USB , SATA x 2
- GB LAN (1000 MB/s) , **DUAL GB-LAN** (opt.)
- PCI-Slot
- (Opt. Extended Temperature Range - 40...+85 ° C)

### 2. Low Power fanless Intel Pentium M Processor (Centrino)

- Socket 478 for Intel **Pentium M Processor** 1.6 GHz
- Hyper Threading Technology
- 533 MHz FSB
- Fanless Operation with Heatpipe
- Intel<sup>®</sup> i915 Chipset
- Gigabit LAN
- 6 x USB-Ports/ 2 Com-Ports
- SATA x 2, **SATA Raid (opt.)**
- PCI-Slot , Mini PCI, PCIe (1), Mini PCIe

### 3. Fanless Intel Core2Duo CPU

- **Socket 478** for Intel **CoreDuo CPU T-2300/T-2500**
- **Socket P** for **Penryn CPU (P-8400)**
- Mobile Intel<sup>®</sup>: 945GM Chipset
- Supports CRT, LVDS, optional TV out or DVI
- Single/Dual GB-LAN, **Triple GB-LAN** (opt.)
- 6 x USB-Ports/ 2 Com-Ports (RS-232/422), (4 opt.)
- SATA x 2, **SATA Raid (opt.)**
- PCI-Slot , Mini PCI, PCIe (1), Mini PCIe

## Environmental

Operating Temperature : 0 .. .50 ° C

Storage : -20 .. .80 ° C

Rel. Humidity : 10% .. 90 % (non-Condensing)

## Approval Dimensions

CE, FCC 2000 x 600 x 60 mm (HxWxD)