



www.ipc-markt.de

HandyCap Media Terminal – Eagle-HA



Superslim Media Terminal in a Aluminum Housing System

Adjustable Height for Handy Capped Use (from 45 – 125 cm)

including fanless Industrial - PC

- 17 or 19" - High Brightness TFT
- Brightness up to 600 cd/qm
- Pentium M or Core2Duo CPU
- Hard-Disk 200 GB
- Ethernet, RS-232, LPT1-Port
- High Definition Audio
- Touchscreen Option

PC- Specification

Intel Socket 478 Pentium M Processor 1.8 GHz
or Core2Duo CPU

Hyper Threading Technology

Fanless Operation with Passive Cooler

Core Logic

Mobile Intel®; Q35 Chipset + ICH8
RAM up to 4 GB
Dual LAN 10/100/1000 Base TX

- eSATA RAID onBoard
- * BIOS Award Bios

Front Side Bus

FSB 800/1066/1333 MHz

Memory

2 x 184 Pins DIMM support 4 GB DDR DRAM (max)

Onboard LCD/VGA Controller

Chip with on-die 256 MB memory
Support LVDS -LCDPanel & Dual CRT display

Multi I/O

Onboard Winbond W 83627 HF Chip

Support:

- * 1 x SPP, EPP /ECP Parallel Port by Pin Header
- * 1 x RS-232 Com 1/ 1 x RS-232/422/485 (Jumper select)

LAN Controller

10/100/1000 Base TX WOL

USB

Onboard 6 x USB ports by Pin header

Audio Realtek ALC888 High Definition Audio.

SSD

Up to 36 GB SSD – no rotating parts

Hardware Monitoring

Winbond W82627 HF Chip, Monitoring of CPU,
System Temperature, Voltage

Watch Dog Timer

16 Levels Software programmable

Environmental

Operating Temperature : 0 .. .60 ° C

Storage : -20 ...80 ° C

Rel. Humidity : 10% .. 90 % (non-Condensing)

Dimensions

2000 x 600 x 60 mm (HxWxD)

Approvals :

CE, FCC