



www.ipc-markt.de

19" Media Terminal Eagle

The optimum Viewing Point on Exhibitions & Public Places



Superslim Media Aluminum Housing System

- 19" - High Brightness TFT
- Brightness up to 600 cd/qm
- Viewing Angle 170/ 150 (V/H)
- Stainless Steel Keyboard (Option)
- Stereo Speakers
- Touchscreen (Option)

including fanless Industrial - PC

- **Intel ATOM / PentiumM or Core2Duo CPU**

Specification CPU

1. Ultra Low Power fanless on Board Intel Single or Dual Core Atom Processor

- Intel® 945GM Chipset
- 2 x RS/232, LPT1, 4 x USB , SATA x 2
- GB LAN (1000 MB/s) , **DUAL GB-LAN** (opt.)
- PCI-Slot
- (Opt. Extended Temperature Range - **40...+85 ° C**)

2. Low Power fanless Intel Pentium M Processor (Centrino)

- Socket 478 for Intel **Pentium M Processor** 1.6 GHz
- Hyper Threading Technology
- 533 MHz FSB
- Fanless Operation with Heatpipe
- Intel® i915 Chipset
- Gigabit LAN
- 6 x USB-Ports/ 2 Com-Ports
- SATA x 2, **SATA Raid (opt.)**
- PCI-Slot , Mini PCI, PCIe (1), Mini PCIe

3. Fanless Intel Core2Duo CPU

- **Socket 478** for Intel **CoreDuo CPU T-2300/T-2500**
- **Socket P** for **Penryn CPU (P-8400)**
- Mobile Intel® 945GM Chipset
- Supports CRT, LVDS, optional TV out or DVI
- Single/Dual GB-LAN, **Triple GB-LAN** (opt.)
- 6 x USB-Ports/ 2 Com-Ports (RS-232/422), (4 opt.)
- SATA x 2, **SATA Raid (opt.)**
- PCI-Slot , Mini PCI, PCIe (1), Mini PCIe

Environmental

Operating Temperature : 0 .. 50 ° C
 Storage : -20 ... 80 ° C
 Rel. Humidity : 10% .. 90 % (non-Condensing)

Dimensions

2000 x 600 x 60 mm (HxWxD)

Approval Color :

CE, FCC RAL 9006

Eagle without Keyboard

Various Options (Card Reader etc)

