



www.ipc-markt.de

Fanless 1- HE - Rack-PC with Single or Dual Intel ATOM CPU Depth only 200



Features

Fanless 1 U- Rackserver with Mini-ITX Mainboard

- Intel 82945G Express Chipsatz (Intel 950 GMA)
- Ultra Low Power (18W only)
- Fanless with Heatpipe
- **Depth only 200 mm**

Specification

* **OnBoard Intel Single or Dual Atom CPU (Silverthorne 45nm), (1.6 GHz) – fanless with Heatpipe**

* **L2 Cache : 1 or 2 x 500 KB**

* **RAM :** 1 GB Dual DDR-II 667/533 MHz, non-ECC unbuffered (240pin DIMM) - up to 2 GB max

* **Integrated VGA**

Intel 82945G Express Chipsatz (Intel 950 GMA)

LAN

ICH7M integrated 10/100 BaseT Ethernet

Audio Realtek High Definition Audio

USB 2.0

- 4x USB 2.0
- 2x PS/2
- 1x Parallel
- 1 x D-SUB15 (VGA)

Connectors external

- 1 x RS232
- 4 x USB 2.0
- 1 x LAN 10/100MBit
- 3x Sound (Line Out,Line In, Microphone)

internal

PCI, USB 2.0 5/6, Audio
2x SATA-II, 1x IDE , supports 2 ports

Serial Ports

Two RS-232 ports

Expansion Slot PCI

1 Slot with RiserCard

Power Connector 20 Pin ATX, P4-Connector



Mechanical

- **Server-Chassis 1 HE**
 - **1 x Internal 2 1/2" Drive**
 - **Slim DVD Combo LW**
 - **Frontdisplay : Power, HD**
 - **Temp.-Range : 0-60 Grad C**
 - **Shock-Operating : 2.5 G @ 15-20ms nonoperating : 36 G**
 - **Dimensions**
483 x 200 x 44,5 mm (B x T x H)
- * **Fanless Power Supply : 90-240 VAC or 12/24 VDC (optional)**