

## Industrial Monitor HI-22W

The Versatile 22" Widescreen TFT Monitor



### Features


- Coated, antiglare Security Glas Panel
- Excellent Brightness & Contrast
- 24/7 Operation (Dauerbetrieb)
- 4 Industrial Inputs :  
VGA, DVI, S-Video, Video Composite
- **16:10 Presentation**
- VESA- Holder
- Panel Mounting
- Full Metall Sheet Chassis for optimal electrical and thermal protection

Model NO.	HI-22W	
Viewing Area	22"	Widescreen
Touchscreen		Option
Resolution	1680 x 1050	WSXGA
Eff. Display Area	475 x 297	mm
Colors	16,7 Mio	
Response Time	3/3 ms	
Contrast Ratio	3000 : 1	
Brightness	300 cd/qm	
Viewing Angle	H 170 x V160	
Input Signal	Analog VGA / DVI / S-Video Comp. Video	
Input Connector	D-sub 15pin / DVI /Cinch	
Scan Frequency	H:30- 94 KHz V: 50-80Hz	
Power Mgmt	VESA DPMS Standard	
Consumption	50W @12VDC Opt. Extern. 12 V Adapt.	
Dimensions (mm)	See Drawing	
Op. Temperature	0-50 Degr. C	
Weight	6,9KG	
Standard	IP-65 (Front)	(Optional)

### Optional Accessories



#### Holder for Mini-IPC Back-Site Mounting



#### Swingarm

#### Additional : Wallmount Kit

#### 22" Panel-Mounting

