

## Industrial Monitor HI-22LED

### The Versatile 22" Full HD TFT Monitor



### Features


- Coated, antiglare Security Glas Panel
- **Background LED (50.000 h Lifetime)**
- 3 Years Warranty
- 24/7 Operation (Dauerbetrieb)
- 5 Industrial Inputs :  
HDMI, VGA, DVI, S-Video, Video Composite
- **Full HD 1920 x 1080 Presentation**
- Excellent Brightness & Contrast
- AIP-Technologie, Picture in Picture (PIP), 3D Comp Filter, Deinterlacing, Noise Suppression, EcoSmart Sensor)
- Adjustable Picture Proportions
- Pivot Function
- Built in Loudspeakers
- VESA- Holder
- Panel Mounting
- Full Metall Sheet Chassis for optimal electrical and thermal protection

Model NO.	HI-22LED	
Viewing Area	22" Widescreen	
Touchscreen		nn
Resolution	1920 x 1080	Full HD
Eff. Display Area	475 x 297 mm (21,5" )	
Colors	16,7 Mio	
Response Time	3/3 ms	
Contrast Ratio	2.000.000 : 1	
Brightness	300 cd/qm	
Viewing Angle	H 170 x V160	
Input Signal	HDMI/DVI/ Analog VGA	S-Video/Comp.Video Audio In/Out
Input Connector	HDMI / DVI / D-sub 15pin /	Cinch / Audio In /Out
Scan Frequency	H:30- 94 KHz	V: 50-80Hz
Power Mgmt	VESA DPMS	Standard
Consumption	50W @12VDC	Extern. 12 V Adapt.
Dimensions (mm)	See Drawing	
Op. Temperature	0 - 45 Degr. C	
Weight	6,9KG	
Standard	IP-65 (Front)	(Optional)

### Optional Accessories



#### Holder for Mini-IPC Back-Site Mounting



**Swingarm**

#### Additional : Wallmount Kits ( fix or turnable)



#### 22" Panel-Mounting

