

## HI-32MT

### Industrial Multitouchscreen Monitor



### Features

- Excellent Brightness & Contrast
- Optical Touchscreen Technology
- NeoV™ Touch Glas-Surface
- 5 Inputs :  
VGA, DVI, S-Video,  
Video Composite, Component Video
- PIP-, PBP- and VOV-Funktion
- Integrated Speakers
- Remote Control
- VESA- Holder
- Horizontal / vertical Mounting (Pivot)
- Outdoor-Full Metall Sheet Chassis

Model NO.	HI - 32MT	
Viewing Area	32" Widescreen	
Touchscreen		Optical USB
Resolution	1920x1080	
Eff. Display Area	698 x 392	mm
Colors	16,7 Mio	
Response Time	6/6 ms	
Contrast Ratio	5000 : 1	
Brightness	450 cd/qm	
Viewing Angle	H 178 x V178	
Input Signal	Analog VGA / S-Video	DVI Comp. Video
Input Connector	D-sub 15pin /	DVI /Cinch
Scan Frequency	H: 49 KHz	V: 60 Hz
Power Mgmt	VESA DPMS	Standard
Consumption	130W	
Dimensions (mm)	768x458x113	WxHxD mm
Op. Temperature	0-50 Degr. C	
Weight	17 KG	
Standard	IP-65 (Front)	(Optional)

### Optional Accessories



Holder for Mini-IPC  
Back-Site Mounting

### Mounting Options



Optional : Wallmount Kit

Table Stand Type A  
-Landscape (Option)



Table Stand Type B – Portrait/ Landscape