

## Industrial Touchscreen Monitor HI-32-P-T

### Multimedia Widescreen TFT (16 : 10)

#### with horizontal and Portrait-Presentation

### Features

- Excellent Brightness & Contrast
- Infrared Touchscreen
- 6 Inputs :  
HDMI, VGA, DVI, S-Video,  
Video Composite, Component  
Video
- **16:12 Presentation**
- VESA- Holder
- Horizontal/vertical Mounting
- Full Metall Sheet Chassis



Model NO.	HI-32-P-T	
Viewing Area	32"	Widescreen
Touchscreen	Infrared via	USB
Resolution	1366 x 768 / 1900 x 1200 (interl)	
Eff. Display Area	698 x 392	mm
Colors	16,7 Mio	
Response Time	8/8 ms	
Contrast Ratio	4000 : 1	
Brightness	450 cd/qm	
Viewing Angle	H 178 x V178	
Input Signal	Analog VGA / S-Video	DVI / HDMI Comp. Video
Input Connector	D-sub 15pin /	DVI /Cinch
Scan Frequency	H: 49 KHz	V: 60 Hz
Power Mgmt	VESA DPMS	Standard
Consumption	130W	
Dimensions (mm)	768x458x113	WxHxD mm
Op. Temperature	0-50 Degr. C	
Weight	19 KG	
Standard	IP-65 (Front)	(Optional)

### Optional Accessories



Holder for Mini-IPC  
Back-Site Mounting

### Mounting Options



Optional : Wallmount Kit

Table Stand Type A  
-Landscape (Option)



Table Stand Type B – Portrait/ Landscape