

IEC-745A

Half-size, 4-slot Wallmount Chassis

Wide model with
PISA (half-size PCI/ISA)
or ISA Backplane



General Specifications

Construction

heavy-duty steel.

Disk Drive Capacity

one 3½" HDD and one 3½" FDD

Control Switches & Indicators

power switch on backpanel
HDD and power LED on front panel

Connectors

5-pin DIN keyboard connector on front panel

Cooling Fan

49 CFM cooling fan on front panel with air filter

Dimensions

172 (W) x 167 (H) x 256 (D) mm.

Weight

2.9 Kg

Environmental

Operating temperature

0 ~ 55°C (storage 0 ~ 70°C)

Humidity

5 to 95% non-condensing

Vibration (operating)

5 to 17 Hz, 0.1" double-amplitude displacement; 17 to 500 Hz, 1.5 G acceleration peak

Shock (operating)

10 G acceleration peak (11 ms duration)

Safety

UL/CSA/TÜV/CE/FCC apprvd.

EMI

meets FCC/VDE Class A

Power Supply Options

IPS-SNP-8071-A

70 W Power Supply (custom size)

V_{INPUT} : 90~132 V_{AC} or 180~264 V_{AC}
@ 47~63 Hz, auto-switching

V_{OUTPUT} (max. load) : +5 V @ 12 A,
+12 V @ 2.6 A, -5 V @ 0.5 A, -12V @ 0.3 A
 V_{OUTPUT} (min. load) : +5V @ 0 A, +12 V @ 0 A

Passive Backplane Options

PBI-4SC

4-slot ISA-bus Passive Backplane

PBP-4S

4-slot PISA-bus Passive Backplane

3 x PCI, 1 x PISA

Ordering

IEC-745A-S4C-FR70 : Half-size Wallmount Chassis with 4-slot ISA Passive Backplane and 110 Watt Power Supply

IEC-745A-P4-FR70 : Half-size Wallmount Chassis with 4-slot PISA Passive Backplane and 110 Watt Power Supply

