

# IEC-747

## Half-size, 4-slot Wallmount Chassis

High model with  
PISA (half-size PCI/ISA)  
or ISA Backplane



### General Specifications

#### Construction

heavy-duty steel.

#### Disk drive housing

one 3½" HDD

#### Control switches

Power switch on backpanel

#### Cooling Fan

49 CFM cooling fan on front panel with air filter

#### Dimensions

150 (W) x 196 (H) x 241.5 (D) mm.

#### Weight

2.9 Kg

### Environmental

#### Operating Temperature

0 ~ 55°C (storage 0 ~ 70°C)

#### Humidity

5 to 95% non-cond.

#### Vibration (operating)

5 to 17 Hz, 0.1" double-amplitude displacement; 17 to 500 Hz, 1.5 G acceleration peak to peak

#### Shock (operating)

10 G acceleration peak (11 ms duration)

#### Safety

UL/CSA/TÜV/CE/FCC apprvd.

#### EMI

Meets FCC/VDE Class A



### Power Supply Options

#### IPS-MRW-170

65 W Power Supply (custom size)

$V_{\text{INPUT}} : 100 \sim 240 V_{\text{AC}}$

@ 47~63 Hz, auto-switching

$V_{\text{OUTPUT}}$  (max. load) : +5 V @ 7 A,

+12 V @ 2.5 A, -12V @ 2.5 A

### Passive Backplane Options

#### PBI-4SC

4-slot ISA-bus Passive Backplane

#### PBP-4S

4-slot PISA-bus Passive Backplane

3 x PCI, 1 x PISA

### Ordering

**IEC-747-S4C-FR65** : Half-size Wallmount Chassis with 4-slot ISA Passive Backplane and 65 Watt Power Supply

**IEC-747-P4-FR65** : Half-size Wallmount Chassis with 4-slot PISA Passive Backplane and 65 Watt Power Supply

