

# IEC-200

## 2U Rackmount Server

ATX motherboard or Backplane  
with 6-slot "Butterfly" Riser Card



### General Specifications

#### Dimensions

430 x 88.5 (2U) x 450 WxHxD mm

#### Weight

Netto 7.9 kg (17.4 lbs)

(without backplane, drives and power supply )

#### Color

Black

#### Construction

Heavy-duty steel chassis

#### Disk drive bay

one 5¼" drivebay for CDROM (accessible from front panel) and two 3½" drives (one accesible from front)

#### Cooling fans

2 heavy duty 42.5 CFM ball bearing fans, two on front panel and one on each side panel

#### Controls on Front Panel

Power On/Off switch, RESET button

#### Indicators on Front panel

Power ON, HDD activity, Fan

#### Connector on Front panel

Pre-wired 5-pin DIN connector for keyboard

#### Motherboard option

Single or Dual full-size ATX motherboard

#### Passive backplane option

optional 6-slot ISA or PCI/ISA backplane

### Power Supply Options

#### IPS-ZKS-250A

250W PS/2 AT Standard Power Supply

$V_{INPUT}$ : 95~130  $V_{AC}$  or 180~260  $V_{AC}$

@ 47 ~ 63Hz, switchable

$V_{OUTPUT}$  (max): +5V @ 25 A, +12V @ 10A, -

5V @ 0.5A, -12V @ 0.5A

$V_{OUTPUT}$  (min): +5V @ 1.0A, +12V @ 0.4A

#### IPS-ZKS-250WX

250W PS/2 ATX Power Supply

$V_{INPUT}$ : 95~130 VAC or 180~260 VAC @47 ~ 63Hz, Switchable

$V_{OUTPUT}$  (max): +5V @ 25A, +12V @ 12A, -

5V @ 0.5A, -12V @ 1.0A, +3.3V @ 14A,

+5VSB @ 1.5A

$V_{OUTPUT}$  (min): +5V @ 3.0A, +12V @ 2.0A,

+3.3V @ 0.2A

#### IPS-ZKS-300WX

300W PS/2 ATX Power Supply

$V_{INPUT}$ : 95~130 VAC or 180~260 VAC @47 ~ 63Hz, Switchable

$V_{OUTPUT}$  (max): +3.3V @ 20A, +5V @ 30A,

12V @ 12A, -15 @ 0.5A, -12V @ 1A, +5VSB

@ 1.5A

$V_{OUTPUT}$  (min): +3.3V @ 0.2A, +5V @ 3A,

+12V @ 2A

### Environmental

#### Operating Temperature

0~45°C (0~75°C non-operating)

#### Altitude

3000 m (10,000 ft.)

#### Shock

2.5G @ 15-20ms

(35G @ 15-20ms non-operating)

#### Vibration

5 ~ 17 Hz, 0.1" double amplitude displace-

ment; 17 ~ 500 Hz, 1.5 G acceleration

(operating and non-operating)



Single or Dual full-size  
ATX motherboard or  
Passive backplane option

250 Watt  
ATX Power  
Supply



2x heavy duty  
cooling fans  
with air filter

1x 5¼" and  
2x 3½" drivebays

Power On/Off, RESET,  
Power and HDD LED  
and Keyboard connector

## ORDERING

**IEC-200A-B** : 2U Rackmount Chassis  
for ATX Motherboard (black)

**IEC-200A-B-AX250** : 2U Rackmount  
Chassis with 250W PS/2 ATX Power (black)

**IEC-200BI-B** : 2U Rackmount Chassis  
with ISA Riser Card (black)

**IEC-200BI-B-R6I** : 2U Rackmount Chassis,  
with 6-slot ISA Riser card (black)

**IEC-200BI-B-R6IAX250** : 2U Rackmount  
Chassis with 6-slot ISA Riser card and  
250W PS2 ATX Power Supply (black)

**IEC-200BP-B** : 2U Rackmount Chassis,  
Black for ISA/PCI Riser Card (black)

**IEC-200BP-B-R6P** : 2U Rackmount Chassis  
with 6-slot ISA/PCI Riser card (black)

**IEC-200BP-B-R6PAX250** : 2U Rackmount  
Chassis with 6-slot ISA/PCI Riser card and  
250W PS2 ATX Power Supply (black)

