# RM241/RM242 2U Feature-advanced Industrial Server Chassis



RM24100/24200 with 2-door Front Bezel

# Features & Benefits (RM24100)

- 18" short depth for missions critical in telecommunication, health care, surveillance and other industries.
- Modular 3-slot full height or 7-slot low profile rear window for flexible configuration
- Cushion on 3.5" and 2.5" HDD holders for minimized HDD vibration
- Removable HDD cage and 3.5" and 2.5" HDD holders for easy installation
- · Slideway design for HDD cage installation and removal
- Support standard components on motherboard, PSU, and 5.25" drive bay for an economical buildup

# Specification

Model Name	· RM24100
M/B Form Factor	· ATX (12" x 9.6")
Dimension (D x W x H)	· 457.2 x 430 x 88.1 mm, 18" x 16.9" x 3.5"
Drive Bay	• Exposed: 1 x 5.25",1x 3.5"
	• Internal: 2 x 3.5", 2 x 2.5"
PSU Form Factor	• PS/2 or 2U single
Indicator	• 1x Power Status, 1x HDD Activity
	· 2x LAN Activity
Front Control	• Power On/Off
	System Reset, 2x USB 2.0
Front Bezel	· Aluminum Plate, Two-piece bezel with air filter (option)
Cooling Fan	• Rear: 1 x 80mm ( T=32mm ),PWM
	• Rear: 2 x 40 mm ( option)
Slot Opening	3x Full Height or 7x Low Profile
HDD Backplane	· N/A
Metal Thickness	• 1.0 mm
Security	Intrusion switch (option)
Front bezel	· option
Dust-proof	· Yes ( only with front bezel )
Slide Rail	• Option
Net Weight	• 6.93 Kg
Gross Weight	· 9.35 Kg
Cubic Feet	· 2.5
Container Info.	· 20' 388 pcs , 40' 788 pcs , 40H' 940 pcs
(Single Packing)	

# Features & Benefits (RM24200)

- 18" short depth for critical missions in telecommunication, health care, surveillance and other industries.
- Delicate in-line layout of front fan and CPU fan for utilized cooling performance on Intel's latest platform
- Modular and removable HDD cages for flexible configuration and easy installation
- · Slideway design for HDD cage installation and removal
- Cushion on 2.5" HDD holders for minimized HDD vibration
- Support standard components on motherboard, PSU, and  $5.25^{\prime\prime}$  drive bay for an economical buildup

### Specification

Model Name	· RM24200
M/B Form Factor	· Micro ATX (9.6" x 9.6")
Dimension (D x W x H)	· 457.2 x 430 x 88.1 mm, 18" x 16.9" x 3.5"
Drive Bay	• Exposed: 1 x 3.5" , 1x Slim ODD
	• Exposed: 2 x 5.25"
	• Internal: 2 x 2.5" w/ damper (option)
PSU Form Factor	• PS/2
Indicator	• 1x Power Status, 1x HDD Activity
	• 2x LAN Activity
Front Control	• Power On/Off, System Reset,
	• 2x USB 2.0
Front Bezel	Aluminum Plate, Two-piece bezel with air filter (option)
Cooling Fan	• Front: 1 x 80mm ( T=32mm ),PWM
	· Rear: 2 x 40mm ( option)
Slot Opening	• 4 x Low Profile PCI
HDD Backplane	• N/A
Metal Thickness	• 1.0 mm
Security	Intrusion switch (option)
Front bezel	• option
Dust-proof	Yes ( only with front bezel )
Slide Rail	• Option
Net Weight	• 6.86 Kg
Gross Weight	• 9.26 Kg
Cubic Feet	· 2.5
Container Info.	· 20' 388 pcs , 40' 788 pcs , 40H' 940 pcs
(Single Packing)	