

## CPC 1700 Kompakt Panel CPC 1700T 17" Touch Monitor

### 17" Fanless Panel PC



**Feature :**  
 Intel Atom / VIA solution, Fanless, Touch screen, Water Proof,  
 Open-frame design, CCFL Backlight

**Application:**  
 Information Kiosk, POS, Mobile solution, Automation control

**Panel PC Information**

LCD Panel	AUO
Resolution	SXGA 1280 x 1024
Brightness ( cd/m <sup>2</sup> )	350
Contrast Ratio	1000 : 1
Backlight	CCFL
Number of Colors	16.7 M
Touch Screen	AMT 8 wires / Resistive touch screen
Mounting Spec.	VESA 75 / 100
Panel frame water proof	IP65
Webcam ( Option )	5.0 Mega pixel - auto focus
Accessory ( Option )	Wall Mount Kit / Stand

**Fanless Panel PC :**

. Panel PC Dimension	79.5 H x 413 W x 343 D mm ( For Lex STD M/B )
	64.5 H x 413 W x 343 D mm ( For 3.5" M/B )
. Case Dimension	
(For Lex STD MB)	71 H x 386.2 W x 316.4 D mm ( Wall mount type )
	71 H x 413 W x 328.9 D mm ( All in one type )
(For 3.5" M/B)	56 H x 386.2 W x 316.4 D mm ( Wall mount type )
	56 H x 413 W x 328.9 D mm ( All in one type )
. Front Panel Dimension	8.5 H x 413 W x 343 D mm
. Material	Plastics front frame + Aluminum
. Weight	4.8 Kg ( Incl. M/B )
. Storage Space	2.5" / 3.5" HDD
. Operation Humidity	5 ~ 90% @ 39 °C, non-condensing

M/B information: ( Please refer to M/B specification )



CPU Type	M/B Model	VGA	COM	LAN	USB	Audio	KB/MS	Others	Operation Temp.	
									CF Card	HDD
Intel Atom N270	3I270L	-	6	1	2	YES	-	-	50°	50°
Intel Core 2 Duo Socket M	CI945C	1	6	2	4	YES	YES	DVI	-	50°
	MI945A	1	2	2	4	YES	YES	DVI / TV-Out / Video-In	-	50°

**More Functions**

Aluminum / Stainless Case	Capacitive touch	Webcam	Parallel Port
DC +6V to +36V	High Brightness Panel	1 ~ 4 Video-IN	Bluetooth
Rechargeable Battery	DIO	Speaker	Wi-Fi
3G	4 x COM	H.264 decode	USB

**Dimension** Wall mount type

