

Mini-ITX Chassis- & Mounting Options for embedded Industrial Computers



Fanless Mini-ITX Chassis

- 1 or 2 or 3 PCI-Slots
- Disk Drive Bays : 1 or 2 or 3 Drives 2 ½”
2 external, 1 internal
- 1 Slim DVD Drive
- 2 Removable Frames for SATA Drives (Option)-
prepared for RAID
- 2 Units fit in one 19” Rack (2HU)
- Internal Power Supply 110-220vAV or 11-26VDC

Dimensions :

225 x 215 x 98 (138) mm (WxHxD) (3 x PCI)



Fanless 1HU Rack Chassis (19” Mounting)

Disk Drive Bays 1 or 2 or 3 Drives 2 ½”
2 external, 1 internal or 2 Drive and Slim DVD Drive
1 PCI-Slot with RiserCard
Optional 1 : Removable Frame for SATA Drives
Internal Power Supply 110-220vAV or 11-26VDC

Dimensions

483,6 x 44,5 x 300 mm (WxHxD)

Fanless 1HU Rack Chassis (19” Mounting)

Disk Drive Bays 1 or 2 or 3 Drives 2 ½”
1 external, 1 internal or 2 Drive and Slim DVD Drive
1 PCI-Slot with RiserCard
Optional 1 :Removable Frame for SATA Drives
Internal Power Supply 110-220vAV or 11-26VDC

Dimensions

483,6 x 44,5 x 220 mm (WxHxD)



Fanless 1 HU Frontloading Rack Chassis (19” Mounting)

(all Connectors to Front Site)

Disk Drive Bays 1 or 2 Drives 2 ½”
1 external Drive and Slim DVD Drive
1 PCI-Slot with RiserCard
Optional : 1ext. Removable Frame for SATA Drives
Internal Power Supply 110-220vAV or 11-26VDC

Dimensions

483,6 x 44,5 x 220 mm (WxHxD)

Mini-IPC Mounting Options



1 Unit in a 19"-Rack 2HU



2 Units in a 19"-Rack 2HU with Telescope Rails



DIN Rail Mounting



Wall Mounting



TFT- Back-Site Mounting