

**19" Rack Server with Motherboard for Intel Dual Core CPU's
with Dual LAN**

Fanless with Heatpipe



Features

Fanless 1 U- Rackserver with Mini-ITX Mainboard

- **Depth only 300 mm**
- Chipset 945GM/ICH7
- Integrated Intel GMA950 Graphics
- Support Intel Viiv Technology
- 6 x USB 2.0 / Firewire
- **Dual LAN** (100 MB/ GigaBit)
- sATA RAID/ eSATA / SATA II
- 7.1 Audio (ALC882M)
- 1 x PCI Slot , 1 PCIe Slot
- optional **12/24 VDC Input**

Specification

- * **Socket 479 for Intel Core Duo/ Solo CPU's (fanless)**
- * **RAM** Dual DDR-II 667/533 MHz, non-ECC, unbuffered
(240 pin DIMM) up to 2 GB
- * **Expansion** : 1x PCI with RiserCard
- * **Graphics** : Integrated Intel GMA950
- * **Intel ICH7 South Bridge** :
1x UltraDMA 100/66/33, 1 x sATA
- * **Audio**: Realtek ALC 882M, 8ch High-Definition Audio CODEC
(Dolby Master Studio, Dolby Prologic IIX, Dolby Head-
phone, Dolby Virtual Speaker, Dolby Digital Live
- * **Primary LAN**
ICH7M integrated 10/100 BaseT Ethernet
- * **Secondary LAN**
Marvell 88E8053 PCI Express Gigabit Ethernet
- * **Rear Panel** : 1x VGA, 2x USB, 1x IEEE 1394,
2 x RJ45, 1x PS/2 Keyboard, 1x PS/2 Mouse, 1x optical S/PDIF
Out, 1x Coax S/PDIF out, 1x 8 channel Audio I/O
- * **Internal Headers** : 2x USB, 1 x IEEE 1394, 1x COM, DVI
1 x S/PDIF In/Out, 1x Game/Midi, Azalia Front Panel Audio, CD Audio In
- * **Optional : removable SATA-Hard Disk Drive**
DVI-Output with Daughterboard
- * **Environmental**
Temperature : 0- 50 Degree C
Humidity : 5 ... 95% noncondensing
- * **Fanless Power Supply**
110- 240 VAC or
12 / 24 VDC (optional)



Mechanical

Drive Bays : 1 x 3 ½" Drive
1 x Slim CD-Rom Drive
Optional SATA Removable Drive

Dimensions : 483,6 x 44,5 x 300
Approval : CE