

**Fanless 1- HE - Rack-PC with Single or Dual  
Intel ATOM CPU**  
Depth only 200



## Features

### Fanless 1 U- Rackserver with Mini-ITX Mainboard

- Intel 82945G Express Chipsatz (Intel 950 GMA)
- Ultra Low Power (18W only)
- Fanles with Heatpipe
- **Depth only 200 mm**

## Specification

\* **OnBoard Intel Single or Dual Atom CPU (Silverthorne 45nm), (1.6 GHz) – fanless with Heatpipe**

\* **L2 Cache : 1 or 2 x 500 KB**

\* **RAM :** 1 GB Dual DDR-II 667/533 MHz, non-ECC unbuffered (240pin DIMM )- up to 2 GB max

\* **Integrated VGA**

Intel 82945G Express Chipsatz (Intel 950 GMA)

#### LAN

ICH7M integrated 10/100 BaseT Ethernet

**Audio** Realtek High Definition Audio

#### USB 2.0

- 4x USB 2.0
- 2x PS/2
- 1x Parallel
- 1 x D-SUB15 (VGA)

#### Connectors external

- 1 x RS232
- 4 x USB 2.0
- 1 x LAN 10/100MBit
- 3x Sound (Line Out,Line In, Microphone

#### internal

PCI, USB 2.0 5/6, Audio  
2x SATA-II, 1x IDE , supports 2 ports

#### Serial Ports

Two RS-232 ports

#### Expansion Slot PCI

1 Slot with RiserCard

**Power Connector** 20 Pin ATX, P4-Connector



## Mechanical

- **Server-Chassis 1 HE**
  - **1 x Internal 2 1/2" Drive**
  - **Slim DVD Combo LW**
  - **Frontdisplay : Power, HD**
  - **Temp.-Range : 0-60 Grad C**
  - **Shock-Operating : 2.5 G @ 15-20ms nonoperating : 36 G**
  - **Dimensions**  
483 x 200 x 44,5 mm (B x T x H)
- \* **Fanless Power Supply : 90-240 VAC or 12/24 VDC (optional)**